

DG-Q3QQ6M

stem	Main Processor	Dual-core 32-bit DSP (XM650V200), pure hard compression, watchdog
	image sensor	2 1/4" high performance CMOS sensors
	Operation System	Embedded LINUX operating system
	Video Compression	Smart H.265X
	APP	ICSEE (Android and IOS support)
Video	High Definition	2*2MP
	Image resolution	Main code stream: 1920*2160@12fps; Substream: 640*720@12fps
	Minimum illumination	0.01 LUX/pro series
	Lens	3.6mm(standard)
	Perspective	92 °
	Turn video	Flip up and down/flip side to side
lighting	Light control mode	Automatic/light on/off/timer/smart alert
	Number of lights	6 red lights +6 white lights
PTZ	PTZ control	Rotation Angle level :355°; Vertical :90°
	Turn PTZ	Flip up and down/flip side to side
Audio	Coding standard	G.711
	Mitou	support
	Two-way Speech	support
Record management	Video file size	Hd video ≈9.7G/ day SD video ≈2.4G/ day
	Record Mode	Manual video recording, dynamic detection video recording, timing video recording, alarm video
	Video storage	TF card/cloud
	storage	Cloud Storage +TF Local Video recording (256GB Max)
	Remote playback	support
	Image capture	support
Network	WIFI	2.4G WIFI 802.11b/g/n
	Pairing	WiFi Smartlink distribution network addition, AP hotspot addition, QR code scanning. Bluetooth fast networking
	Network Protocol	Support TCP/IP, ONVIF, RTSP
extension	Bluetooth remote control	support
	Reset key	support
	Human tracking	support
	360degree coordinate positioning	support
power supply	Power	AC 100-230V
	power interfac	E27 standard base
work environment	Suitable place	outdoor、Home、shop、School、factory ;
	Installation mode	hoisting
	Working Temperature	-20℃— +55℃
	Working humidity	10%— 90%