

EP5-QQ-6M-36X

<b>Camera</b>	
Image Sensor	6MP (3MP+3MP) 1/2.8" CMOS
Solution	XM650V200+2009*2
Mini Illumination	Color 0.01Lux@F1.2(AGC ON), 0 Lux with IR
	Black and White 0.001 Lux @ (F1.2,AGC ON),0 Lux with IR
Digital Noise Reduction	2D/3D DNR
Image Settings	Image Flip
Function	remote monitoring; push message after human detection alarm; image capture
<b>Lens</b>	
Lens	optical zoom lens (4.7-94mm )
Rotate Range	Pan rotation:0~355°, Tilt rotation:0~90°
<b>Rotation</b>	
Angle	Manual control of the rotation adjustment according to the scene to be monitored
Preset Point	Support
<b>Video</b>	
Image Output	Main Stream: 2304*2592@12fps
	Sub-Stream: 640*720@12fps
<b>Audio</b>	
Audio Compression	G.711; Support Two Way Audio
<b>AI+</b>	
General	Human detection, Human tracking, Intrusion alarm, Line crossing detection
Alarm	SD card recording, APP alarm, Sound and light alarm
<b>APP</b>	
Mobile View	Android, IOS ( ICSEE)
<b>Light</b>	
Warm Light Distance	Up to 60 m
IR Distance	Up to 60 m
LEDS	6 PCS IR LEDS +4 PCS White Lights + 6 PCS Dual Wick LEDS
Lighting mode	Starlight full color; Infrared night vision; Intelligent alert
<b>General</b>	
Power Supply	DC 12V±25%
Power Connector	Ø5.5mm
Power consumption	≤12w
Operating Conditions	(-25℃ ~ 45℃) humidity 95% or less (non-condensing)
Factory Data Reset	Support
Material	Plastic
Dimension	Product : 142*182*239mm
	Packing : 160*145*240mm
Weight	Net weight : 580g
	Gross weight : 740g
Accessory	screw kit x1, user manual x1